





WORLD CLASS TRUCK-MOUNTED LOADERS SINCE 1954

PB TRUCK-MOUNTED LOADER





Why use two machines to handle a loading job when there's one machine that can meet your needs? A PB Loader combines a dump turck and a loader into one unit. It's designed to load, haul and dump material with just one machine - so it saves operation costs, reduces manpower and lets you tackle a variety of jobs that would otherwise require several pieces of equipment.

PB Loaders are built tough and come equipped with features that improve productivity and safety. An exclusive

arm design allows the operator access to the cab when the shovel is on the ground or in the travel position. PB Loaders are available with a 3,000 lb or 5,000 lb shovel lifting capacity, and can be outfitted with a clam, tilt, clam/ tilt or standard shovel. Shovel capacities range from 3/4 cubic yard to 1 1/2 cubic yards. Safety switches shut down all systems if the cab door is opened or the dump body is raised during loading operations.



Shoveling Apron for Asphalt, Sand or Other Materials



Emulsion System



Specialized Dump Body



- · Fully hydraulic operation loader operates with one lever from inside truck cab.
- Rugged, durable construction for long-term reliable performance.
- Adaptable to cab-over or conventional truck chassis.
- Truck doors, dump body and loader are all controlled by interlock switches.
- Shovel can be stopped in any position.
- Fast operation cycle - ten seconds.
- Designed for multiple jobs leaf and trash removal, clearing and cleaning gutters, handling utility cuts,





Rigid Construction

www.pblcorp.com

e		loading and hauling gravel, dirt or sand.
	•	Can be equipped with an emulsion spray system for
e		asphalt patching and road repairs.
	•	Popular configurations include standard or tilt shovel,
		with or without clam attachment.
d	•	Many options available to meet your needs - from cab
		shields and dump bodies to hose reels and work lights
		- PB has what you need to get the job done.

PB LOADER SPECIFICATIONS

Loader Models	L-100 L-200	L-100-T L-200-T	L-100-C L-200-C	L-100-CT L-200-CT	L-150 L-250	L-150-T L-250-T	L-150-C L-250-C	L-150-CT L-250-CT
LIFTING CAPACITY	3000 lbs	3000 lbs	3000 lbs	3000 lbs	5000 lbs	5000 lbs	5000 lbs	5000 LBS
SHOVEL CAPACITY	.75 cu yd	.75 cu yd	1 cu yd	1 cu yd	1.25 cu yd	1.25 cu yd	1.5 cu yd	1.5 cu yd
LOADER CYLINDERS	1	1	1	1	2	2	2	2
CLAM CYLINDERS			2	2			2	2
TILT CYLINDERS		1		1		2		2

Key

L-100 = for conventional cabs L-200 = for tilt cabs C = clam attachment T = tilting shovel CT = clam attachment with tilting shovel

PB LOADER

OPTIONS

Air Controls Air-Operated Automatic Retracting Mirrors Arrow Boards Body Covers Bolt-On Cutting Edge

- Cab Shields Carbide Cutting Edge Cone Holders Dump Bodies Emulsion Spray Systems Fire Extinguisher
- Hardened Shovel Sides Hitches Hose Reels Lockable Tool Boxes Shoveling Apron Strobe Lights and Beacons
- Tool Holders Triangle Kits Work Lights



Standard Shovel



Shovel with Clam Attachment



Tilting Shovel



Tilting Shovel with Clam Attachment

